

# A Short Review of Piezoelectricity-based Vibration and Acoustic Energies Harvesting

Bin Li\*

Molex Inc., Auburn Hills, Michigan, USA

**Keywords:** Vibration energy harvesting; Acoustic energy harvesting; Piezoelectricity

## Introduction

The majority of us have been familiar with usage of ambient renewable energies including solar, wind, Thermal and biochemical energies to generate electricity. However, our environment is still full of wasted energies. Vibration [1] and acoustic energies [2] are two of the currently wasted energies. Vibration and acoustic energies are clean and renewable. But unfortunately, output power of vibration and acoustic energies are lower than solar and wind energies. This becomes a main issue for wide practical application of vibration and acoustic energies harvesting. However, vibration and acoustic energies exhibit several special advantages than solar and wind energies. Firstly, harvesting vibration and acoustic energies is not limited by weather and time. Vibration energy largely exists in motions from vehicle and airplane, human body, operating machine, etc. And, acoustic energy can be easily found in noise from traffics, airplane engine, stadium, etc. Ubiquity of vibration and acoustic energies will provide a great number of opportunities to allow us to utilize vibration and acoustic energies. Most importantly, storage of vibration and acoustic energies over a period of time may be significant. This short review aims to illustrate piezoelectricity-based vibration energy harvesting, acoustic energy harvesting, and the related AC/DC circuit design.

## Vibration Energy Harvesting

There has been numerous studies focusing on the conversion of mechanical vibration energy to usable electric energy mostly using piezoelectric materials [3-5]. A piezoelectric material generates an electrical charge when mechanically deformed (i.e., direct piezoelectric effect), or conversely, it physically deforms in the presence of an electric field (i.e., converse piezoelectric effect). It should be mentioned that, piezoelectricity is not the only way to scavenge vibration energy. For example, magnetic generator can also be used for vibration energy harvesting [3]. Since the predominated method for vibration energy harvesting is using piezoelectricity, this short review will only cover piezoelectricity-based vibration energy harvesting.

Many efforts in piezoelectric energy harvesting have sought to scavenge the ambient environmental vibration energy such as air flow, water flow and rain drop. Matova et al. [4] reported an airflow energy harvester using with a Helmholtz resonator combined with a piezoelectric energy converter. The resonator stores and accumulates the airflow energy converted into electrical energy harvester. The maximum power of 42.2  $\mu$ W was obtained when the airflow velocity is 20 m/s. Li et al. [5] experimentally proposed and tested a bioinspired piezo-leaf architecture which converts wind energy into electrical energy by wind induced fluttering motion. The peak output power is approximately 600  $\mu$ W with the maximum power density 2 mW/cm<sup>3</sup> for a single leaf. Erturk et al. [6] studied piezoaeroelasticity for vibration energy harvesting. The electricity is generated at the flutter boundary of a piezoaeroelastic airfoil from aeroelastic vibration. An electrical power output is 10.7 mW at the linear flutter speed of 9.3

m/s. Ovejas et al. [7] developed multimodal energy harvesters from wind to electrical power by piezoelectric films. Taylor et al. [8] used piezoelectric polymers to harvest the mechanical flow energy, available in oceans and rivers, to electricity. The multielement-Eel system is capable of producing 1 W in a nominal 1 m/s water flow. Liu et al. [9] employed an array of similar PZT microcantilevers in a self-sustained flow-sensing microsystem for harvesting wind-driven vibration energy. The output voltage and power were measured as 18.1 mV and 3.3 nW at the flow velocity of 15.6 m/s with the corresponding power density 0.36 mW/cm<sup>3</sup>. Voltages generated by ceramic based piezoelectric fiber composite structures and polymer based piezoelectric strips were investigated by Vatansever et al [10] with varying wind speeds, water droplet weights and releasing heights. It is worth mentioning that piezoelectric arrays have been introduced to increase the harvested vibrational energy [11-13]. Wang et al. [12] proposed a shear mode piezoelectric energy harvester for harvesting energy from pressurized water flow. In their study, an instantaneous output power of 0.45 nW are generated when the excitation pressure oscillates with an amplitude of 20.8 kPa at 45 Hz. The maximum total power was found to be of the order of 0.2  $\mu$ W. Guigon *et al.* [13,14] scavenged the vibration energy using a piezoelectric flexible structure impacted by a water drop. The measurements conducted in various impact situations (different drop heights and drop sizes) show that the quantity of electrical energy that can be recovered using their structure is approximately 1 nJ of electrical energy and 1  $\mu$ W of instantaneous power.

## Acoustic Energy Harvesting

Recently, increasing efforts have been expended on developing mechanisms to harvest acoustic energy available in airports, construction sites, factory, traffics, etc. Acoustic energy harvesters generally are composed of two components: an acoustic resonator and a piezoelectric oscillator. The amplified acoustic wave inside the acoustic resonator drives the oscillation of piezoelectric element and generates electricity. Actually, the electromechanical energy conversion via piezoelectricity in acoustic energy harvesting is same as vibration energy harvesting. Horowitz et al. [15] first developed a micromachined acoustic energy harvester using a Helmholtz resonator with a lead zirconate titanate (PZT) piezoelectric composite diaphragm attached to the resonator's bottom wall. The output power of Horowitz's harvester is ~ 0.1 nW with an incident SPL of 149 dB at 13.6 kHz. Later, Electromechanical Helmholtz resonator (EMHR) has

\*Corresponding author: Bin Li, Molex Inc, Auburn Hills, Michigan, USA, Tel: +1214-768-2000; E-mail: [binlieng@gmail.com](mailto:binlieng@gmail.com)

Received October 28, 2015; Accepted November 10, 2015; Published November 12, 2015

Citation: Li B (2015) A Short Review of Piezoelectricity-based Vibration and Acoustic Energies Harvesting. *Innov Ener Res* 4: e113. doi: 10.4172/2576-1463.1000e113

Copyright: © 2015 Li B. This is an open-access article distributed under the terms of the Creative Commons Attribution License, which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited.

been introduced by Liu and Phipps et al. and also use amplified acoustic wave to deform a PZT piezoelectric back plate [16-18]. The EMHR generated the power of 30 mW when incident 160 dB SPL at 2.6 kHz, Lee et al. [17] developed a Helmholtz resonator with single-layer and multilayer piezoelectric cantilever beams to harvest acoustic energy. The output power of multilayer PVDF composite cantilever is 0.19  $\mu$ W when incident SPL is 118 dB at 850 Hz. In addition to a Helmholtz resonator, a sonic crystal was also used to scavenge acoustic energy [18,19]. A curved polyvinylidene fluoride (PVDF) piezoelectric beam was installed inside a defect region of sonic crystal to acts as a resonant cavity. The output power of sonic crystal acoustic energy harvester is  $\sim$  35 nW with the incident SPL of 80  $\sim$  100 dB at 4.2 kHz. Very recently, a novel and practical acoustic energy harvesting mechanism to harvest a travelling sound at a low audible frequency (180  $\sim$  200Hz) was developed and studied both experimentally and numerically [20-33]. This acoustic energy harvester used a quarter-wavelength straight tube resonator with multiple piezoelectric cantilever plates installed inside the tube. The maximum output power of the acoustic energy harvester is measured as 10.129 mW when the incident sound pressure level is 112 dB.

## Vibration and Acoustic Energies Harvesting Circuit Design

Overall speaking, essentials of piezoelectricity-based vibration and acoustic energies harvesting are both to apply vibration to piezoelectric transducer, and then generate a vibration deformation to create AC electrical output. In piezoelectric energy conversion, the efficiency strongly relies on the impedance of external circuit which converts AC to DC to charge a storage component (e.g., electrochemical battery). A vibrating piezoelectric element (piezoelectric oscillator) generates AC output while the battery generally require a stabilized DC because of the electronic compatibility. Therefore, a high efficient AC/DC conversion external circuit needs to be considered to achieve a high efficiency electromechanical energy conversion.

The most simple AC/DC interface circuit for piezoelectric energy harvesting system is the standard interface circuit [21,22]. In the standard energy harvesting circuit, the piezoelectric element is directly connected to a storage capacitor through a full-bridge rectifier, and the external loading resistance is used to match the impedances of the piezoelectric element with the external circuit in order to maximize the harvested electrical power [23,24]. In addition to the standard energy harvesting circuit, nonlinear electronic interfaces have been developed to increase the energy harvesting efficiency of piezoelectric elements [25]. The synchronized switch harvesting on inductor (SSHI) interface circuit is one of the most important nonlinear electronic interfaces by adding a digital switch and an inductor to the piezoelectric element in series (S-SSHI) and parallel (P-SSHI). In both S-SSHI and P-SSHI, the piezoelectric output voltage is inverted when the switch is triggered at the maximum piezoelectric displacements measured by a displacement sensor. SSHI circuits are found to not only enhance the harvested power by 400~900%, but also broaden the system bandwidth compared with standard circuits [26]. Thus far, most studies focusing on the AC/DC conversions for a single piezoelectric oscillator. In order to realize an AC/DC conversion for multiple piezoelectric oscillators, the effect of external circuits has been investigated both numerically and experimentally [33-36]. Furthermore, the size of vibration and acoustic energy harvesters may need to be minimized to more easily embedded into energy sources. Thus the size and volume effect of electronic components in circuit may need to be considered [27-46] in future circuit design for vibration and acoustic energies harvesting.

## Conclusion

In this short review, piezoelectricity-based vibration and acoustic energies harvesting are discussed in terms of harvester conversion mechanism, operation frequency, output power and potential application aspects. The overview of electronic circuit design is also included to demonstrate AC/DC conversion for vibration and acoustic energies harvesting system.

## References

1. Tang X, Zuo L (2012) Vibration energy harvesting from random force and motion excitations *Smart Mater Struct* 21: 075-025.
2. Pillai MA, Deenadayalan E (2013) A review of acoustic energy harvesting, *International Journal of Precision Engineering and Manufacturing* 15: 949-985.
3. Kim HS, Kim JH, Kim JA (2011) Review of Piezoelectric Energy Harvesting Based on Vibration, *Int J Precis Eng Man.* 12: 1129-41.
4. Anton SR, Sodano HA (2007) A review of power harvesting using piezoelectric materials (2003–2006) *Smart Mater Struct*, 16: R1-21.
5. Saadon S, Sidek O (2011) A review of vibration-based MEMS piezoelectric energy harvesters, *Energ Convers Mmanage.* 52: 500-04.
6. Kim SH, Ji CH, Galle P, Herrault F, Wu X (2009) An electromagnetic energy scavenger from direct airflow, *J Micromech Microeng* 19: 094010.
7. Matova SP, Elfrink R, Vullers RJM, van Schaijk R, et al. (2011) *J Micromech Microeng* 21: 104001.
8. Li S, Yuan J, Lipson H (2011) Ambient wind energy harvesting using cross-flow fluttering, *J Appl Phys*, 109: 026104.
9. Erturk A, Vieira WGR, Marqui CD, Inman DJ (2010) On the energy harvesting potential of piezoaeroelastic systems, *Appl Phys Lett* 96: 184103.
10. Ovejas VJ, Cuadras A (2011) Multimodal piezoelectric wind energy harvesters, *Smart Mater Struct* 20: 085030.
11. Taylor GW, Burns JR, Kammann SM, Powers WB (2001) Welsh TR The Energy Harvesting Eel: A Small Subsurface Ocean/River Power Generator, *IEEE J Oceanic Eng*, 26: 539-47.
12. Liu H, Zhang S, Kathiresan R, Kobayashi T, Lee C (2012) Development of piezoelectric microcantilever flow sensor with wind-driven energy harvesting capability, *Appl Phys Lett*, 100: 223905.
13. Vatanserver D, Hadimani RL, Shah T, Siores E (2011) An investigation of energy harvesting from renewable sources with PVDF and PZT, *Smart Mater Struct*, 20: 055019.
14. Majidi C, Haataja M, Srolovitz DJ (2010) Analysis and design principles for shear-mode piezoelectric energy harvesting with ZnO nanoribbons, *Smart Mater Struct*, 19: 055027.
15. Lien IC and Shu YC (2012) Array of piezoelectric energy harvesting by the equivalent impedance approach, *Smart Mater Struct*, 21: 082001.
16. Liu JQ, Fang HB, Xu ZY, Mao XH, Shen XC, et al. (2008) MEMS-based piezoelectric power generator array for vibration energy harvesting, *Microelectron J*, 39 802-06.
17. Wang DA, Liu NZ (2011) A shear mode piezoelectric energy harvester based on a pressurized water flow, *Sensor Actuat A-Phys*, 167: 449-58.
18. Guigon R, Chaillout JJ, Jager T, Despesse G (2008) Harvesting raindrop energy: theory, *Smart Mater Struct*, 17: 015038.
19. Guigon R, Chaillout JJ, Jager T, Despesse G (2008) Harvesting raindrop energy: experimental study, *Smart Mater Struct*, 17: 015039.
20. Horowitz SB, Sheplak M, Cattafesta LN, Nishida T (2006) A MEMS acoustic energy harvester, *J Micromech Microeng*, 16: S174-81.
21. Liu F, Phipps A, Horowitz S, Ngo K, Cattafesta L, et al. (2008) Acoustic energy harvesting using an electromechanical Helmholtz resonator. *J Acoust Soc Am* 123: 1983-1990.
22. Liu F, Horowitz S, Nishida T, Cattafesta L, Sheplak M (2007) A multiple degree of freedom electromechanical Helmholtz resonator. *J Acoust Soc Am* 122: 291-301.

23. Phipps A, Liu F, Cattafesta L, Sheplak M, Nishida T (2009) Demonstration of a wireless, self-powered, electroacoustic liner system. *J Acoust Soc Am* 125: 873-881.
24. Lee HY, Choi Bumk (2013) A multilayer PVDF composite cantilever in the Helmholtz resonator for energy harvesting from sound pressure, *Smart Mater Struct*, 22: 115025.
25. Wu LY, Chen LW, Liu CM (2009) Acoustic energy harvesting using resonant cavity of a sonic crystal, *Appl Phys Lett*, 95: 013506.
26. Wang WC, Wu LY, Chen LW, Liu CM (2010) Acoustic energy harvesting by piezoelectric curved beams in the cavity of a sonic crystal, *Smart Mater Struct*, 19: 045016.
27. Li B, You JH (2011) Harvesting ambient acoustic energy using acoustic resonators, *Proceedings of Meetings on Acoustics*, 12: 065001.
28. Li B, You JH (2012) Simulation of acoustic energy harvesting using piezoelectric plates in a quarter-wavelength straight-tube resonator, COMSOL Boston conference, Boston.
29. Li B, Laviage A, You JH, Kim YJ (2013) Harvesting low-frequency acoustic energy using quarter-wavelength straight-tube acoustic resonator, *Appl Acoust*, 74: 1271-1278.
30. Li B, Laviage A, You JH, Kim YJ (2012) Acoustic energy harvesting using quarter-wavelength straight-tube resonator, ASME 2012 International Mechanical Engineering Congress & Exposition, IMECE2012-86989.
31. Li B, You JH (2014) Acoustic-structure interaction and eigen frequency shift in acoustic energy harvester, The Smart Structures/NDE conference.
32. Li B, You JH (2015) Experimental study on self-powered SSHI circuits for multiple piezoelectric plates in acoustic energy harvesting, *Journal of Intelligent Material Systems and Structures*, 1045389X14566523.
33. Roundy S, Wright RK, Rabaey JM (2003) Energy scavenging for wireless sensor networks with special focus on vibration, Kluwer academic publishers, Norwell.
34. Kim HS, Kim JH, Kim J (2011) A review of piezoelectric energy harvesting based on vibration, *Int J Precis Eng Man*, 12: 1129-41.
35. Lien IC, Shu YC (2012) Array of piezoelectric energy harvesting by the equivalent impedance approach, *Smart Mater Struct*, 21: 082001.
36. Lien IC, Shu YC, Wu WJ, Shiu SM, Lin HC (2010) Revisit of series-SSHI with comparisons to other interfacing circuits in piezoelectric energy harvesting, *Smart Mater Struct*, 19: 125009.
37. Guyomar D, Lallart M (2011) Recent Progress in Piezoelectric Conversion and Energy Harvesting Using Nonlinear Electronic Interfaces and Issues in Small Scale Implementation, *Micromachines*, 2: 274.
38. Lallart M1, Guyomar D, Richard C, Petit L (2010) Nonlinear optimization of acoustic energy harvesting using piezoelectric devices. *J Acoust Soc Am* 128: 2739-2748.
39. Li B, You JH (2013) Comparison study of standard, conventional SSHI and self-powered SSHI interface circuits in piezoelectric energy conversion, ICAST2013: 24th International Conference on Adaptive Structures and Technologies, Aruba.
40. Li B, You JH, Kim YJ (2013) Self-powered interface circuit for low-frequency acoustic energy harvester, ASME 2013 International Mechanical Engineering Congress & Exposition.
41. Li B, Zhang XP, Yang Y, Yin LM, Pecht MG (2013) Size and constraint effects on interfacial fracture behavior of microscale solder interconnects, *Microelectronics Reliability*, 53: 154-163.
42. Li B, Yin LM, Yang Y, Zhang XP (2010) Size and constraint effects on interfacial fracture behavior of microscale solder interconnects, Size Effects on Interface Fracture Behavior of Lead-free Micro-joints, *Chinese Journal of Mechanical Engineering*, 18: 77-84.
43. Qin HB, Li B, Yue W, Zhang XP (2014) Interaction effect between electromigration and the evolution of eutectic Sn-58Bi Alloy, 64th Electronic Components and Technology Conference (ECTC).
44. Qin HB, Li B, Li XP, Zhang XP (2011) Finite element simulation of fracture behavior of BGA structure solder interconnects, International Conference on Electronic Packaging Technology & High Density Packaging (ICEPT-HDP).
45. Qin HB, Li B, Zhang XP (2010) Finite element simulation of interfacial fracture and impact behavior at the interfaces of microscale Sn-Ag-Cu solder interconnects, International Conference on Electronic Packaging Technology & High Density Packaging (ICEPT-HDP).
46. Qin HB, Yue W, Li B, Ke CB, Zhou MB, et al. (2014) Interaction effect between electromigration and microstructure evolution in BGA structure Cu/Sn-58Bi/Cu solder interconnects, International Conference on Electronic Packaging Technology & High Density Packaging (ICEPT-HDP).